

WOCK®



> Technical Sheet

# BLOC

PURE  
EFFICIENCY



**BLOC 01**  
Navy Blue  
34/35 - 46/47



**BLOC 02**  
Medium Blue  
34/35 - 46/47



**BLOC 03**  
Green  
34/35 - 46/47



**BLOC 04**  
Fuchsia  
34/35 - 42



**BLOC 05**  
White  
34/35 - 46/47



**BLOC 06**  
Yellow  
34/35 - 46/47



**BLOC 11 RECYCLED**  
Black | Black  
34/35 - 46/47

100% RECYCLED



Also available without strap

• BLOC Strap



# BLOC

PURE  
EFFICIENCY



**BLOC** is a one-piece clog designed for long lasting comfort and easy maintenance.

## Description

**BLOC**, is a monocolored occupational clog entirely made of polymeric materials and with the following components:

- Antistatic insert;
- Heel-strap; \*
- Ventilation holes.

## Users

**BLOC**, is ideal for activities in which professionals spend many hours standing and, who hence have a tendency to suffer foot discomfort or lower body fatigue, especially to be used in:

- Operation Room
- Hospitals and Other Healthcare Institutions
- Pharmaceutical Industry

## Specifications

- Sterilizable**  
Produced in a high-quality polymer which allows sterilization in autoclave up to 134 °C for 15 minutes.
- Shock Absorption**  
The special design helps to reduce the occurrence of micro-lesions in tendons, bones and joints, and the feeling of tired legs.
- Antistatic**  
Promotes the dissipation of accumulated static electricity.
- ESD**  
Protects objects and electronic equipment you work with.
- Upper Liquid Protection**  
Avoids the entrance of liquids inside the shoe.
- Removable Strap \***  
Increases comfort and support to the heel, as well as keeps your foot firmly in the footwear.
- Breathable**  
Regulates the temperature and humidity of the foot.
- Washable**  
The footwear can be machine washed up to 90 °C.
- Antislip**  
The sole is designed to reduce the risk of slipping.
- Lemon Scent**  
The footwear has a fresh and soft fragrance, with a lemon scent.
- 100% Recycled (Applies to BLOC 11)**  
Raw material from industrial waste, such as: samples, prototypes, burrs and products that do not meet quality standards.

## Materials and Technologies

**BLOC** is made with **Steri-tech™** technology. Its material allows sterilization up to 134 °C, is non-toxic and provides odor resistance.

The special design of the heel gives unparalleled comfort.

## Technical Standard

- CE**  
Regulation 2016/425
- EN ISO 20347:2012** OB+A+E+SRC
- SATRA TM 158:1992** Washability — 90 °C.



## Technical Specifications

- Heat resistance — autoclavable up to a maximum of 134 °C for 15 minutes;
- Slip-resistant;
- Resistant to abrasion;
- Recyclable.

Chemical resistance Indicatives Material: STERI-TECH®		Chemical resistance Indicatives Material: STERI-TECH®	
Medium	SEBS Grades	Medium	SEBS Grades
WATER	1	SUNFLOWER OIL	3
SALINE SOLUTION	1	BRAKE FLUID	2
ACIDS / BASES		21D / 23°C	2
DETERGENT SOLUTION	1	7D / 70°C	2-3
SOAP SOLUTION	1	PETROL	3-4
CAUSTIC SODA SOLUTION	1	WATER/OIL EMULSION (70°C)	2
POTASSIUM SOLUTION	1	ETHYLENTE GLYCOL, 50% SOLUTION	
AMMONIA	1	10D / 90°C	1
SULFURIC ACID 96%	1	MINERAL OIL	3
NITRIC ACID 10%	1	7D / 23°C	3
HYDROCHLORIC ACID 10%	1	24H / 70°C	3
CILTRIC ACIS 10%	2-3	HYDRAULIC OIL	
LACTIC ACID 10%	1	7D / 23°C	2
HYDROGEN PEROXIDE (6 TO 12%)	2	24H / 70°C	3
ALCOHOLS	1-2	TOLUENE (1H)	2
ALDEHYDES / KETONES	1-2	PETROLETHR (1H)	2
SODIUM CHLORIDE (10% SOLUTION)	1		

Legend: 1 = Excellent; 2 = Good; 3 = Limited; 4 = Not recommended

## Care and Cleaning

**Wash:** Machine washable up to a maximum temperature of 90 °C. Can also be steam sterilized in autoclave up to 134 °C for 15 minutes.

**Dry:** Wipe with a cloth or dry at room temperature.

## Attention

**BLOC** resists to several sterilizations in autoclave, but the durability of the clog depends on following the recommended cleaning and washing instructions. **BLOC** also resists to several washings at 90 °C in washing machine. It is not recommended the use of bleaching agents during washing machine cycles at 90 °C.

\* Only applies to BLOC Strap version.

**WOCK®**

WOCK® is a registered trademark owned by Walkmore, S.A.